


Designación	FORMATO EN LARGO 12.800 (mm)				Peso Kg/m	Paquete		
	Altura H (mm)	Superior ØS (mm)	Inferior ØI (mm)	Transversal ØT (mm)		Uds.	mts.	Tm.
H08 666	80	6	6	4	0,935	88	1.126,4	1,053
H09 666	90	6	6	4	0,947	88	1.126,4	1,067
H09 676	90	7	6	4	1,027	88	1.126,4	1,157
H10 666	100	6	6	4	0,960	88	1.126,4	1,081
H10 676	100	7	6	4	1,040	88	1.126,4	1,171
H10 101010	100	10	10	4	2,145	88	1.126,4	2,416
H12 666	120	6	6	4	0,988	88	1.126,4	1,113
H12 676	120	7	6	4	1,068	88	1.126,4	1,203
H12 878	120	7	8	4	1,414	88	1.126,4	1,593
H12 888	120	8	8	4	1,507	88	1.126,4	1,697
H12 101010	120	10	10	4	2,173	88	1.126,4	2,448
H13 666	130	6	6	4	1,003	88	1.126,4	1,129
H14 666	140	6	6	4	1,018	88	1.126,4	1,147
H14 676	140	7	6	4	1,098	88	1.126,4	1,237
H14 676 Ø5	140	7	6	5	1,294	88	1.126,4	1,457
H14 888	140	8	8	4	1,537	88	1.126,4	1,731
H15 666	150	6	6	4	1,034	88	1.126,4	1,165
H17 666	170	6	6	4	1,067	88	1.126,4	1,201
H17 676	170	7	6	4	1,147	88	1.126,4	1,291
H17 686 Ø5	170	8	6	5	1,462	88	1.126,4	1,647
H18 676	180	7	6	4	1,163	88	1.126,4	1,310
H20 666	200	6	6	4	1,118	88	1.126,4	1,259
H20 666 Ø5	200	6	6	5	1,369	88	1.126,4	1,541
H20 676	200	7	6	4	1,198	88	1.126,4	1,349
H20 676 Ø5	200	7	6	5	1,449	88	1.126,4	1,632
H20 868	200	6	8	4	1,464	88	1.126,4	1,649
H20 878	200	7	8	4	1,544	88	1.126,4	1,739
H22 666	220	6	6	4	1,153	88	1.126,4	1,298
H22 676	220	7	6	4	1,233	88	1.126,4	1,389
H23 666	230	6	6	4	1,171	88	1.126,4	1,318
H23 676	230	7	6	4	1,251	88	1.126,4	1,409
H23 888	230	8	8	4	1,690	88	1.126,4	1,903
H24 676	240	7	6	4	1,268	88	1.126,4	1,429
H25 666	250	6	6	4	1,207	88	1.126,4	1,359
H25 666 Ø5	250	6	6	5	1,507	88	1.126,4	1,697
H25 676	250	7	6	4	1,287	88	1.126,4	1,449
H25 676 Ø5	250	7	6	5	1,587	88	1.126,4	1,787
H27 666	270	6	6	4	1,243	88	1.126,4	1,400
H28 666	280	6	6	4	1,261	88	1.126,4	1,421
H28 676	280	7	6	4	1,341	88	1.126,4	1,511
H28 888	280	8	8	4	1,780	88	1.126,4	2,005
H30 666	300	6	6	4	1,298	50	640,0	0,831
H30 666 Ø5	300	6	6	5	1,650	50	640,0	1,056
H30 676	300	7	6	4	1,378	50	640,0	0,882



ØT = 4,0 / 5,0 (mm)

B = 90 (mm)

P = 200 (mm)

Acero Calidad B500T

